

View Online at <https://aerobasegroup.com/nsn/4140-01-296-4952>

**Speed Adjustments:**

Two speed

**Length:**

2.000 inches

**Ambient Temperature At Full Rated Power:**

-10.0 degrees celsius and 70.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3350.0

**Drive Type:**

Direct

**Air Flow Rate:**

240.0 cubic feet per minute

**Voltage In Volts And Current Type:**

24.0 dc or 56.0 dc

**Prime Mover Power Rating:**

22.0 watts

**Housing Inside Diameter:**

6.750 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Special Features:**

Venturi-single piece, die-cast aluminum, painted black; propeller and terminal cover - polycarbonate, black, meeting ul94v-0 flammability rating; per military standard 461 meets emi standards per fcc part 15, subpart j of docket 20780, class a and b radiated and conducted emissions, meets emi standards per vde specification 0871/6.78 for category a and b requirements

**Material:**

Aluminum housing

**Unpackaged Unit Weight:**

1.840 pounds

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0