

View Online at <https://aerobasegroup.com/nsn/4140-01-296-7168>

**Speed Adjustments:**

Single speed

**Length:**

2.000 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Shock proof

**Ambient Temperature At Full Rated Power:**

135.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2850.0 and 3300.0

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

190.0 cubic feet per minute and 220.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

23.0 watts and 21.0 watts

**Housing Inside Diameter:**

5.920 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

50.0 and 60.0

**Material:**

Aluminum alloy

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0