

View Online at <https://aerobasegroup.com/nsn/4140-01-300-8058>

Speed Adjustments:

Single speed

Length:

26.000 inches

Flow Direction:

Outward

Environmental Protection:

Dripproof and explosion proof and waterproof

Ambient Temperature At Full Rated Power:

65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange and 36 unthreaded hole

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

2000.0 cubic feet per minute

Voltage In Volts And Current Type:

440.0 ac

Prime Mover Power Rating:

1.500 horsepower

Housing Inside Diameter:

15.500 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

60.0

Material:

Steel housing

Surface Treatment:

Chromate zinc

Style Designator:

Fixed

Specification Or Standard:

X-a type

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0

Mil-std (military Standard):

Mil-f-18953 spec.