

View Online at <https://aerobasegroup.com/nsn/4140-01-304-0130>

**Speed Adjustments:**

Single speed

**Width:**

3.140 inches

**Length:**

1.500 inches

**Flow Direction:**

Outward

**Environmental Protection:**

Humidity proof and salt spray resistant and shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 100.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2800.0 and 3200.0 and 3600.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

30.0 cubic feet per minute and 34.0 cubic feet per minute and 37.0 cubic feet per minute

**Voltage In Volts And Current Type:**

10.8 dc or 12.0 dc or 13.2 dc

**Prime Mover Power Rating:**

2.9 watts

**Housing Inside Diameter:**

2.500 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Height:**

3.140 inches

**Material:**

Aluminum alloy

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0