

View Online at <https://aerobasegroup.com/nsn/4140-01-306-2029>

Speed Adjustments:

Single speed

Length:

3.120 inches

Flow Direction:

Inward

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

31.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Housing Inside Diameter:

2.820 inches

Phase:

Three

Special Features:

Fan shall meet the emi requiremens of parts 1 and 2 of mil-std-461 for class a1b and shall meet the environmental requirements of mil-e-5400t for class ii equipment with the following exceptions tailored to the a-7d-k application: temperaure (operating) -54 to +73 degrees c cont., +90 degrees c short-time, +95 degrees c intermittent; altitude 50000 ft; vibration (random) fig. 6 of Itv 9-51240/7r-047, (gunfire) fig. 15 and 16 of Itv 9-51240/7r-047; acceleration x porm 4g, y porm 2.5g, z +7g-5g

Frequency In Hertz:

400.0

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0