

View Online at <https://aerobasegroup.com/nsn/4140-01-314-7124>

**Speed Adjustments:**

Single speed

**Ambient Temperature At Full Rated Power:**

-54.0 degrees celsius and 210.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3250.0

**End Application:**

Module, electronic support (iec)

**Electrical Connection Type:**

Connector

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Prime Mover Type:**

Electric motor

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

220.0 cubic feet per minute

**Voltage In Volts And Current Type:**

25.0 ac

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Three

**Frequency In Hertz:**

60.0

**Material:**

Aluminum housing

**Surface Treatment:**

Enamel lusterless

**Surface Treatment Specification:**

Mil-c-5541 military specification single treatment response

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0

**Mil-std (military Standard):**

Mil-c-5541 spec.