NSN 4140-01-316-2217

Tubeaxial Fan - Page 1 of 2

Speed Adjustments:

Single speed



View Online at https://aerobasegroup.com/nsn/4140-01-316-2217

| Length: |
|--|
| 2.000 inches |
| Flow Direction: |
| Inward |
| Ambient Tempurature At Full Rated Power: |
| 70.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 3350.0 |
| Electrical Connection Type: |
| Terminal |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 2 ring |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Features Provided: |
| Thermal protective device |
| Air Flow Rate: |
| 240.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 208.0 ac |
| Prime Mover Power Rating: |
| 34.0 watts |
| Housing Inside Diameter: |
| 6.000 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Phase: |
| Three |
| Frequency In Hertz: |
| 400.0 |
| Material: |
| Plastic polycarbonate blade |

NSN 4140-01-316-2217

Tubeaxial Fan - Page 2 of 2



| Unpackaged Unit Weight: |
|-------------------------|
| 1.840 pounds |
| Style Designator: |
| Fixed |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

No

Fiig:

A087a0