NSN 4140-01-318-2432



| vaneaxial Fan - Page 1 of 2 |
|---|
| View Online at https://aerobasegroup.com/nsn/4140-01-318-2432 |
| Speed Adjustments: |
| Two speed |
| Length: |
| 22.000 inches |
| Flow Direction: |
| Inward |
| Ambient Tempurature At Full Rated Power: |
| 70.0 degrees celsius |
| Operating Speed At Rated Capacity In Rpm: |
| 1800.0 |
| Electrical Connection Type: |
| Terminal box |
| Static Pressure At Specificationified Air Flow Rate: |
| 0.0 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Type And Quantity: |
| 2 flange |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Air Flow Rate: |
| 2750.0 cubic feet per minute |
| Voltage In Volts And Current Type: |
| 440.0 ac |
| Prime Mover Power Rating: |
| 2.000 horsepower |
| Housing Inside Diameter: |
| 18.875 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Ball |
| Phase: |
| Three |
| Frequency In Hertz: |

60.0

Material:

Aluminum alloy 356.0 housing

Material Specification:

Qq-a-601 federal specification single material response blade

NSN 4140-01-318-2432

Vaneaxial Fan - Page 2 of 2



| 01-1- | D = =! = 1 = | |
|-------|--------------|--|
| Stvie | Designator: | |
| | | |

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A087a0