

View Online at <https://aerobasegroup.com/nsn/4140-01-325-2954>

Speed Adjustments:

Single speed

Length:

1.730 inches

Flow Direction:

Inward

Environmental Protection:

Shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-30.0 degrees celsius and 100.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

5000.0

Electrical Connection Type:

Terminal

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 ring

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

80.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

24.7 watts

Housing Inside Diameter:

3.562 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

400.0

Material:

Aluminum

Unpackaged Unit Weight:

1.250 pounds

Surface Treatment:

Enamel lusterless

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0