

View Online at <https://aerobasegroup.com/nsn/4140-01-325-2954>

**Speed Adjustments:**

Single speed

**Length:**

1.730 inches

**Flow Direction:**

Inward

**Environmental Protection:**

Shock proof and vibration proof

**Ambient Temperature At Full Rated Power:**

-30.0 degrees celsius and 100.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

5000.0

**Electrical Connection Type:**

Terminal

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

2 ring

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

80.0 cubic feet per minute

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

24.7 watts

**Housing Inside Diameter:**

3.562 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Phase:**

Single

**Frequency In Hertz:**

400.0

**Material:**

Aluminum

**Unpackaged Unit Weight:**

1.250 pounds

**Surface Treatment:**

Enamel lusterless

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0