NSN 4140-01-336-7086

Centrifugal Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-01-336-7086

Speed Adjustments: Single speed Width: 2.590 inches Length: 9.640 inches Environmental Protection: Humidity proof and salt spray resistant and shock proof and vibration proof Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead Outlet Inside Width:
Width: 2.590 inches Length: 9.640 inches Environmental Protection: Humidity proof and salt spray resistant and shock proof and vibration proof Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
2.590 inches Length: 9.640 inches Environmental Protection: Humidity proof and salt spray resistant and shock proof and vibration proof Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
Length: 9.640 inches Environmental Protection: Humidity proof and salt spray resistant and shock proof and vibration proof Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
9.640 inches Environmental Protection: Humidity proof and salt spray resistant and shock proof and vibration proof Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
Environmental Protection: Humidity proof and salt spray resistant and shock proof and vibration proof Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
Humidity proof and salt spray resistant and shock proof and vibration proof Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
Ambient Tempurature At Full Rated Power: -25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
-25.0 degrees fahrenheit and 150.0 degrees fahrenheit Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
Operating Speed At Rated Capacity In Rpm: 2900.0 Electrical Connection Type: Wire lead
2900.0 Electrical Connection Type: Wire lead
Electrical Connection Type: Wire lead
Wire lead
Outlet Inside Width:
2.110 inches
Outlet Inside Height:
2.500 inches
Static Pressure At Specificationified Air Flow Rate:
0.0 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
Fully enclosed
Mounting Facility Type And Quantity:
1 flange
Rotation Direction For Which Designed:
Clockwise
Air Flow Rate:
245.0 cubic feet per minute
Outlet Location:
Тор
Voltage In Volts And Current Type:
115.0 ac
Prime Mover Power Rating:
300.0 watts
Prime Mover Drive Shaft Bearing Type:
Ball
Discharge Direction:

Vertical down

NSN 4140-01-336-7086

Centrifugal Fan - Page 2 of 2



Phase:
Single
Frequency In Hertz:
50.0 and 60.0
Height:
8.620 inches
Material:
Steel
Surface Treatment:
Zinc blade
Style Designator:
Fixed, rectangular outlets
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A087a0