## NSN 4140-01-336-7086

Centrifugal Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-01-336-7086

| Speed Adjustments:  Single speed  Width:  2.590 inches  Length:  9.640 inches  Environmental Protection:  Humidity proof and salt spray resistant and shock proof and vibration proof  Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead  Outlet Inside Width: |
|---|
| Width:  2.590 inches  Length:  9.640 inches  Environmental Protection:  Humidity proof and salt spray resistant and shock proof and vibration proof  Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead   |
| 2.590 inches  Length:  9.640 inches  Environmental Protection:  Humidity proof and salt spray resistant and shock proof and vibration proof  Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead   |
| Length:  9.640 inches  Environmental Protection:  Humidity proof and salt spray resistant and shock proof and vibration proof  Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead   |
| 9.640 inches  Environmental Protection:  Humidity proof and salt spray resistant and shock proof and vibration proof  Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead  |
| Environmental Protection:  Humidity proof and salt spray resistant and shock proof and vibration proof  Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead  |
| Humidity proof and salt spray resistant and shock proof and vibration proof  Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead   |
| Ambient Tempurature At Full Rated Power:  -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm:  2900.0  Electrical Connection Type:  Wire lead  |
| -25.0 degrees fahrenheit and 150.0 degrees fahrenheit  Operating Speed At Rated Capacity In Rpm: 2900.0  Electrical Connection Type:  Wire lead   |
| Operating Speed At Rated Capacity In Rpm: 2900.0  Electrical Connection Type:  Wire lead  |
| 2900.0  Electrical Connection Type:  Wire lead  |
| Electrical Connection Type: Wire lead   |
| Wire lead   |
|   |
| Outlet Inside Width:  |
|   |
| 2.110 inches  |
| Outlet Inside Height:   |
| 2.500 inches  |
| Static Pressure At Specificationified Air Flow Rate:  |
| 0.0 inches of water   |
| Drive Type:   |
| Direct  |
| Prime Mover Type:   |
| Electric motor  |
| Inclosure Type:   |
| Fully enclosed  |
| Mounting Facility Type And Quantity:  |
| 1 flange  |
| Rotation Direction For Which Designed:  |
| Clockwise   |
| Air Flow Rate:  |
| 245.0 cubic feet per minute   |
| Outlet Location:  |
| Тор   |
| Voltage In Volts And Current Type:  |
| 115.0 ac  |
| Prime Mover Power Rating:   |
| 300.0 watts   |
| Prime Mover Drive Shaft Bearing Type:   |
| Ball  |
| Discharge Direction:  |

Vertical down

## NSN 4140-01-336-7086

Centrifugal Fan - Page 2 of 2



| Phase:                     |
|----------------------------|
| Single                     |
| Frequency In Hertz:        |
| 50.0 and 60.0              |
| Height:                    |
| 8.620 inches               |
| Material:                  |
| Steel                      |
| Surface Treatment:         |
| Zinc blade                 |
| Style Designator:          |
| Fixed, rectangular outlets |
| Shelf Life:                |
| N/a                        |
| Unit Of Measure:           |
|                            |
| Demilitarization:          |
| No                         |
| Fiig:                      |

A087a0