

View Online at <https://aerobasegroup.com/nsn/4140-01-341-0588>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Inward

Environmental Protection:

Shock proof and vibration proof

Ambient Temperature At Full Rated Power:

0.0 degrees celsius and 71.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3100.0

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

210.0 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

35.0 watts

Housing Inside Diameter:

5.920 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Single

Frequency In Hertz:

60.0

Material:

Plastic polycarbonate bladealuminum alloy housing

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0