

View Online at <https://aerobasegroup.com/nsn/4140-01-347-6168>

Speed Adjustments:

Single speed

Length:

2.000 inches

Flow Direction:

Outward

Environmental Protection:

Explosion proof and humidity proof and shock proof and vibration proof

Ambient Temperature At Full Rated Power:

-54.0 degrees celsius and 55.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3400.0

Electrical Connection Type:

Connector

Static Pressure At Specificationified Air Flow Rate:

0.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 rim

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

230.0 cubic feet per minute

Voltage In Volts And Current Type:

200.0 ac

Prime Mover Power Rating:

40.0 watts

Housing Inside Diameter:

5.920 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Phase:

Three

Frequency In Hertz:

400.0

Material:

Aluminum

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0