NSN 4140-01-348-5859

Vaneaxial Fan - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4140-01-348-5859

| Speed Adjustments: |
|--|
| Two speed |
| Length: |
| 22.000 inches |
| Operating Speed At Rated Capacity In Rpm: |
| 1750.0 |
| Electrical Connection Type: |
| Terminal box |
| Static Pressure At Specificationified Air Flow Rate: |
| 1.5 inches of water |
| Drive Type: |
| Direct |
| Prime Mover Type: |
| Electric motor |
| Inclosure Type: |
| Partially enclosed |
| Mounting Facility Type And Quantity: |
| 16 unthreaded hole |
| Rotation Direction For Which Designed: |
| Counterclockwise |
| Air Flow Rate: |
| 3000.0 cubic feet per minute |
| Criticality Code Justification: |
| Zzzy |
| Voltage In Volts And Current Type: |
| 440.0 ac |
| Prime Mover Power Rating: |
| 3.000 horsepower |
| Housing Inside Diameter: |
| 15.520 inches |
| Prime Mover Drive Shaft Bearing Type: |
| Sleeve |
| Phase: |
| Three |
| Frequency In Hertz: |
| 60.0 |
| Material: |
| Aluminum housing |
| Style Designator: |
| Fixed |
| Reference Number Differentiating Characteristics: |
| Ordist an autism to test of face and marries are as |

Quiet operation tested for submarine usage

NSN 4140-01-348-5859

Vaneaxial Fan - Page 2 of 2



| _ | | | | | |
|---|-----|------|---|--------|--|
| c | hο | JIF. | | .ife: | |
| J | 116 | | _ | .II C. | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0