

View Online at <https://aerobasegroup.com/nsn/4140-01-351-3168>

**Length:**

22.906 inches

**Environmental Protection:**

Spray tight

**Ambient Temperature At Full Rated Power:**

149.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

1800.0

**Outlet Inside Width:**

4.188 inches

**Outlet Inside Height:**

11.312 inches

**Static Pressure At Specificationified Air Flow Rate:**

2.5 inches of water

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

400.0 cubic feet per minute

**Criticality Code Justification:**

Zzzx

**Outlet Location:**

Top

**Voltage In Volts And Current Type:**

440.0 ac

**Prime Mover Power Rating:**

0.750 horsepower

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Phase:**

Three

**Special Features:**

Magnetic permeability shall not exceed 2.0 after fabrication

**Frequency In Hertz:**

60.0

**Material:**

Aluminum alloy 6061 blade

**Surface Treatment:**

Chromate housing inside and varnish housing inside

**Surface Treatment Specification:**

Tt-p-645 federal specification 1st treatment response and tt-v-119 federal specification 2nd treatment response

**Style Designator:**

Fixed, rectangular outlets

**Specification Or Standard:**

Cc type

**Departure From Cited Designator (non-core):**

Magnetic permeability shall not exceed 2.0 after fabrication

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0