

View Online at <https://aerobasegroup.com/nsn/4140-01-351-3168>

Length:

22.906 inches

Environmental Protection:

Spray tight

Ambient Temperature At Full Rated Power:

149.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

1800.0

Outlet Inside Width:

4.188 inches

Outlet Inside Height:

11.312 inches

Static Pressure At Specificationified Air Flow Rate:

2.5 inches of water

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

400.0 cubic feet per minute

Criticality Code Justification:

Zzzx

Outlet Location:

Top

Voltage In Volts And Current Type:

440.0 ac

Prime Mover Power Rating:

0.750 horsepower

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Phase:

Three

Special Features:

Magnetic permeability shall not exceed 2.0 after fabrication

Frequency In Hertz:

60.0

Material:

Aluminum alloy 6061 blade

Surface Treatment:

Chromate housing inside and varnish housing inside

Surface Treatment Specification:

Tt-p-645 federal specification 1st treatment response and tt-v-119 federal specification 2nd treatment response

Style Designator:

Fixed, rectangular outlets

Specification Or Standard:

Cc type

Departure From Cited Designator (non-core):

Magnetic permeability shall not exceed 2.0 after fabrication

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0