

View Online at <https://aerobasegroup.com/nsn/4140-01-358-5141>

**Environmental Protection:**

Corrosion resistant and dustproof and fungus resistant

**Ambient Temperature At Full Rated Power:**

-40.0 degrees fahrenheit and 150.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

22500.0

**End Application:**

Pacer special

**Electrical Connection Type:**

Connector receptacle

**Prime Mover Type:**

Electric motor

**Rotation Direction For Which Designed:**

Clockwise

**Voltage In Volts And Current Type:**

200.0 ac

**Prime Mover Power Rating:**

100.0 watts

**Phase:**

Three

**Special Features:**

Designed for environment generated by nuclearweapons, electrically bonded to the aircraft chassis/mil-b-5087, class r

**Frequency In Hertz:**

400.0

**Material:**

Stainless steel housing

**Quantity:**

1

**Surface Treatment:**

Anodize blade

**Surface Treatment Specification:**

Mil-r-8625, type ii, class 1 military specification single treatment response blade

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A087a0

**Mil-std (military Standard):**

Mil-r-8625 spec.