

View Online at <https://aerobasegroup.com/nsn/4140-01-475-1272>

Speed Adjustments:

Single speed

Length:

13.000 inches

Flow Direction:

Outward

Environmental Protection:

Spray tight

Ambient Temperature At Full Rated Power:

65.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3450.0

End Application:

Arleigh burke class ddg

Electrical Connection Type:

Terminal block

Static Pressure At Specificationified Air Flow Rate:

0.7 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

2 flange

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

380.000 cubic feet per minute

Voltage In Volts And Current Type:

115.0 ac

Prime Mover Power Rating:

0.066 horsepower

Housing Inside Diameter:

13.000 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Blade Shape:

Forward curve

Err Default:

Err default

Phase:

Single

Special Features:

Type/model designation: 11/2 a1w6, as modified by push button or rotary switch

Frequency In Hertz:

60.0

Material:

Steel housing

Unpackaged Unit Weight:

60.000 pounds

Style Designator:

Fixed

Type/model Designation (non-core):

L1/2 a1w6

Specification Data:

81349-mil-f-18953 government specification

Departure From Cited Designator (non-core):

As modified by push button or rotary switch

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0