NSN 4140-01-483-6138

Tubeaxial Fan - Page 1 of 2

Speed Adjustments:



View Online at https://aerobasegroup.com/nsn/4140-01-483-6138

Single speed
Width:
3.130 inches
Length:
1.150 inches
Flow Direction:
Outward
Operating Speed At Rated Capacity In Rpm:
3150.0
End Application:
Test set, reentry system rsts replacement program
Electrical Connection Type:
Wire lead
Static Pressure At Specificationified Air Flow Rate:
0.27 inches of water
Drive Type:
Direct
Prime Mover Type:
Electric motor
Inclosure Type:
Open
Mounting Facility Type And Quantity:
Mounting Facility Type And Quantity: 4 lug
4 lug
4 lug Rotation Direction For Which Designed:
4 lug Rotation Direction For Which Designed: Clockwise
4 lug Rotation Direction For Which Designed: Clockwise Air Flow Rate:
4 lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute
4 lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type:
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating:
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter:
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter: 2.815 inches
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter: 2.815 inches Prime Mover Drive Shaft Bearing Type:
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter: 2.815 inches Prime Mover Drive Shaft Bearing Type: Sleeve
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter: 2.815 inches Prime Mover Drive Shaft Bearing Type: Sleeve Product Name:
A lug Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter: 2.815 inches Prime Mover Drive Shaft Bearing Type: Sleeve Product Name: Fan, axial, ac
Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter: 2.815 inches Prime Mover Drive Shaft Bearing Type: Sleeve Product Name: Fan, axial, ac Shaft Bearing Type:
Rotation Direction For Which Designed: Clockwise Air Flow Rate: 35.9 cubic feet per minute Voltage In Volts And Current Type: 115.0 ac or 230.0 ac Prime Mover Power Rating: 10.5 watts Housing Inside Diameter: 2.815 inches Prime Mover Drive Shaft Bearing Type: Sleeve Product Name: Fan, axial, ac Shaft Bearing Type: Sleeve

NSN 4140-01-483-6138

Tubeaxial Fan - Page 2 of 2



Frequency In Hertz
60.0
Height:
3.130 inches
Material:
Steel
Style Designator:
Fixed
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A087a0