

View Online at <https://aerobasegroup.com/nsn/4140-01-506-4547>

**Stage Quantity:**

1

**Speed Adjustments:**

Single speed

**Width:**

19.000 inches

**Length:**

9.500 inches

**Ambient Temperature At Full Rated Power:**

-20.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

3250.0

**End Application:**

Test set

**Electrical Connection Type:**

Cord w/attached plug

**Outlet Inside Width:**

4.880 inches

**Outlet Inside Height:**

4.000 inches

**Static Pressure At Specificationified Air Flow Rate:**

0.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise and counterclockwise

**Features Provided:**

Radio interference shielding and louver

**Air Flow Rate:**

470.0 cubic feet per minute

**Outlet Location:**

Center

**Voltage In Volts And Current Type:**

115.0 ac

**Prime Mover Power Rating:**

185.0 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Product Name:**

Kpr729b emi/rfi shielded twin packaged blowers

**Phase:**

Single

**Frequency In Hertz:**

60.0

**Height:**

8.750 inches

**Material:**

Steel

**Quantity:**

2

**Surface Treatment:**

Phosphate housing and enamel housing

**Style Designator:**

Fixed, dual, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0