

View Online at <https://aerobasegroup.com/nsn/4140-01-514-5656>

**Speed Adjustments:**

Single speed

**Width:**

19.000 inches

**Length:**

14.000 inches

**Environmental Protection:**

Corrosion resistant

**Ambient Temperature At Full Rated Power:**

-20.0 degrees fahrenheit and 250.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

1500.0

**End Application:**

R-iais, 4920014959100

**Electrical Connection Type:**

Cord w/attached plug

**Outlet Inside Width:**

4.560 inches

**Outlet Inside Height:**

5.630 inches

**Static Pressure At Specificationified Air Flow Rate:**

1.0 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

1 flange

**Rotation Direction For Which Designed:**

Clockwise and counterclockwise

**Air Flow Rate:**

800.0 cubic feet per minute

**Outlet Location:**

Center

**Voltage In Volts And Current Type:**

230.0 ac

**Prime Mover Power Rating:**

260.0 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Angular up

**Product Name:**

Blower, twin packaged, emi shielded

**Shaft Bearing Type:**

Ball

**Phase:**

Single

**Special Features:**

Mfg name kpr1051 emi/rfi shielded twin packaged blowers, weight - 40lbs, permanent washable filter, exhaust guards, stainless steel grilles, 6 foot power cord

**Frequency In Hertz:**

50.0 and 60.0

**Height:**

12.250 inches

**Material:**

Steel housing

**Quantity:**

2

**Surface Treatment:**

Enamel baked housing

**Style Designator:**

Fixed, dual, rectangular outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0