

View Online at <https://aerobasegroup.com/nsn/4140-01-514-5656>

Speed Adjustments:

Single speed

Width:

19.000 inches

Length:

14.000 inches

Environmental Protection:

Corrosion resistant

Ambient Temperature At Full Rated Power:

-20.0 degrees fahrenheit and 250.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

1500.0

End Application:

R-iais, 4920014959100

Electrical Connection Type:

Cord w/attached plug

Outlet Inside Width:

4.560 inches

Outlet Inside Height:

5.630 inches

Static Pressure At Specificationified Air Flow Rate:

1.0 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

1 flange

Rotation Direction For Which Designed:

Clockwise and counterclockwise

Air Flow Rate:

800.0 cubic feet per minute

Outlet Location:

Center

Voltage In Volts And Current Type:

230.0 ac

Prime Mover Power Rating:

260.0 watts

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Angular up

Product Name:

Blower, twin packaged, emi shielded

Shaft Bearing Type:

Ball

Phase:

Single

Special Features:

Mfg name kpr1051 emi/rfi shielded twin packaged blowers, weight - 40lbs, permanent washable filter, exhaust guards, stainless steel grilles, 6 foot power cord

Frequency In Hertz:

50.0 and 60.0

Height:

12.250 inches

Material:

Steel housing

Quantity:

2

Surface Treatment:

Enamel baked housing

Style Designator:

Fixed, dual, rectangular outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0