

View Online at <https://aerobasegroup.com/nsn/4140-01-516-5710>

Speed Adjustments:

Single speed

Width:

4.690 inches

Length:

1.500 inches

Environmental Protection:

Vibration proof and weatherproof

Ambient Temperature At Full Rated Power:

-85.0 degrees fahrenheit and 185.0 degrees fahrenheit

Operating Speed At Rated Capacity In Rpm:

1800.0

End Application:

An/syk2 (v) , t on tomahawk missile

Electrical Connection Type:

Connector plug

Static Pressure At Specificationified Air Flow Rate:

0.14 inches of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Features Provided:

Safety impeller guard

Air Flow Rate:

83.0 cubic feet per minute

Outlet Location:

Center

Voltage In Volts And Current Type:

12.0 dc

Prime Mover Power Rating:

30.0 watts

Housing Inside Diameter:

4.130 inches

Prime Mover Drive Shaft Bearing Type:

Ball

Discharge Direction:

Horizontal

Height:

4.690 inches

Material:

Aluminum alloy or stainless steel

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0