

View Online at <https://aerobasegroup.com/nsn/4140-01-516-5710>

**Speed Adjustments:**

Single speed

**Width:**

4.690 inches

**Length:**

1.500 inches

**Environmental Protection:**

Vibration proof and weatherproof

**Ambient Temperature At Full Rated Power:**

-85.0 degrees fahrenheit and 185.0 degrees fahrenheit

**Operating Speed At Rated Capacity In Rpm:**

1800.0

**End Application:**

An/syk2 (v) , t on tomahawk missile

**Electrical Connection Type:**

Connector plug

**Static Pressure At Specificationified Air Flow Rate:**

0.14 inches of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Features Provided:**

Safety impeller guard

**Air Flow Rate:**

83.0 cubic feet per minute

**Outlet Location:**

Center

**Voltage In Volts And Current Type:**

12.0 dc

**Prime Mover Power Rating:**

30.0 watts

**Housing Inside Diameter:**

4.130 inches

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Discharge Direction:**

Horizontal

**Height:**

4.690 inches

**Material:**

Aluminum alloy or stainless steel

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0