

View Online at <https://aerobasegroup.com/nsn/4140-01-520-7383>

**Width:**

15.625 inches

**Length:**

11.500 inches

**Operating Speed At Rated Capacity In Rpm:**

3450.0

**Electrical Connection Type:**

Cord w/attached plug

**Outlet Inside Diameter:**

6.000 inches

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

4 bolt

**Rotation Direction For Which Designed:**

Clockwise

**Outlet Location:**

Center

**Voltage In Volts And Current Type:**

115.0 ac or 230.0 ac

**Prime Mover Power Rating:**

1.500 horsepower

**Discharge Direction:**

Horizontal

**Phase:**

Single

**Special Features:**

Blower hazardous location motor are approved for class i, group d and class ii, groups f and g hazardous locations--have steel blower wheels --suitible for low-pressure applications, have cast aluminum housings to guard against corrosion--spark-resistant construction, direct drive motors, and housings that adjust to 4 outlets postions--inlet and outlets are round--has (4) 3/8 mounting holes on base.

**Frequency In Hertz:**

60.0

**Height:**

13.312 inches

**Material:**

Steel blade

**Style Designator:**

Fixed, round outlets

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0