

View Online at <https://aerobasegroup.com/nsn/4140-01-520-7383>

Width:

15.625 inches

Length:

11.500 inches

Operating Speed At Rated Capacity In Rpm:

3450.0

Electrical Connection Type:

Cord w/attached plug

Outlet Inside Diameter:

6.000 inches

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

4 bolt

Rotation Direction For Which Designed:

Clockwise

Outlet Location:

Center

Voltage In Volts And Current Type:

115.0 ac or 230.0 ac

Prime Mover Power Rating:

1.500 horsepower

Discharge Direction:

Horizontal

Phase:

Single

Special Features:

Blower hazardous location motor are approved for class i, group d and class ii, groups f and g hazardous locations--have steel blower wheels --suitible for low-pressure applications, have cast aluminum housings to guard against corrosion--spark-resistant construction, direct drive motors, and housings that adjust to 4 outlets postions--inlet and outlets are round--has (4) 3/8 mounting holes on base.

Frequency In Hertz:

60.0

Height:

13.312 inches

Material:

Steel blade

Style Designator:

Fixed, round outlets

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0