

View Online at <https://aerobasegroup.com/nsn/4140-01-527-0913>

Speed Adjustments:

Single speed

Diameter:

5.290 inches

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

50.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

3400.0

Electrical Connection Type:

Wire lead

Drive Type:

Belt

Prime Mover Type:

Electric motor

Inclosure Type:

Fully enclosed

Mounting Facility Type And Quantity:

8 threaded insert

Rotation Direction For Which Designed:

Counterclockwise

Air Flow Rate:

170.0 cubic feet per minute

Voltage In Volts And Current Type:

24.0 dc

Prime Mover Power Rating:

26.0 watts

Prime Mover Drive Shaft Bearing Type:

Ball

Shaft Bearing Type:

Ball

Special Features:

12/28 vdc operating voltage range; 1.100 amps running current; 2.000 amps locked rotor current; 26 watts running power; 57.1 dba noise; die cast aluminum motor base; black plastic ul94v-0 propeller; operating temperature -10/+70 degrees c; 12 inch lead-wires, 22 awg; designed for continuous duty life of 35, 000 hours at 50 degrees c

Material:

Plastic blade

Style Designator:

Curved blades double width

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A087a0