

View Online at <https://aerobasegroup.com/nsn/4140-01-527-0913>

**Speed Adjustments:**

Single speed

**Diameter:**

5.290 inches

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

50.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

3400.0

**Electrical Connection Type:**

Wire lead

**Drive Type:**

Belt

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Fully enclosed

**Mounting Facility Type And Quantity:**

8 threaded insert

**Rotation Direction For Which Designed:**

Counterclockwise

**Air Flow Rate:**

170.0 cubic feet per minute

**Voltage In Volts And Current Type:**

24.0 dc

**Prime Mover Power Rating:**

26.0 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Shaft Bearing Type:**

Ball

**Special Features:**

12/28 vdc operating voltage range; 1.100 amps running current; 2.000 amps locked rotor current; 26 watts running power; 57.1 dba noise; die cast aluminum motor base; black plastic ul94v-0 propeller; operating temperature -10/+70 degrees c; 12 inch lead-wires, 22 awg; designed for continuous duty life of 35,000 hours at 50 degrees c

**Material:**

Plastic blade

**Style Designator:**

Curved blades double width

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A087a0