

View Online at <https://aerobasegroup.com/nsn/4140-01-536-9385>

Speed Adjustments:

0 to full speed

Width:

Between 119.5 millimeters and 120.5 millimeters

Length:

Between 37.5 millimeters and 38.5 millimeters

Flow Direction:

Outward

Ambient Temperature At Full Rated Power:

-10.0 degrees celsius and 60.0 degrees celsius

Operating Speed At Rated Capacity In Rpm:

2900.0

End Application:

436-7403893- (1z496) , processor unit, cams

Electrical Connection Type:

Wire lead

Static Pressure At Specificationified Air Flow Rate:

7.0 millimeters of water

Drive Type:

Direct

Prime Mover Type:

Electric motor

Inclosure Type:

Partially enclosed

Mounting Facility Type And Quantity:

4 unthreaded hole

Rotation Direction For Which Designed:

Clockwise

Air Flow Rate:

3360.0 liters per minute

Voltage In Volts And Current Type:

12.0 dc

Prime Mover Power Rating:

5.0 watts

Prime Mover Drive Shaft Bearing Type:

Ball

Special Features:

Available with variable speed, speed sensor, and alarm; this item has a third wire (blue) which is a hook-up for the locked motor sensor; weight is 256.0 g.

Height:

Between 119.5 millimeters and 120.5 millimeters

Material:

Plastic

Style Designator:

Fixed

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A087a0