

View Online at <https://aerobasegroup.com/nsn/4140-01-536-9385>

**Speed Adjustments:**

0 to full speed

**Width:**

Between 119.5 millimeters and 120.5 millimeters

**Length:**

Between 37.5 millimeters and 38.5 millimeters

**Flow Direction:**

Outward

**Ambient Temperature At Full Rated Power:**

-10.0 degrees celsius and 60.0 degrees celsius

**Operating Speed At Rated Capacity In Rpm:**

2900.0

**End Application:**

436-7403893- (1z496) , processor unit, cams

**Electrical Connection Type:**

Wire lead

**Static Pressure At Specificationified Air Flow Rate:**

7.0 millimeters of water

**Drive Type:**

Direct

**Prime Mover Type:**

Electric motor

**Inclosure Type:**

Partially enclosed

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Rotation Direction For Which Designed:**

Clockwise

**Air Flow Rate:**

3360.0 liters per minute

**Voltage In Volts And Current Type:**

12.0 dc

**Prime Mover Power Rating:**

5.0 watts

**Prime Mover Drive Shaft Bearing Type:**

Ball

**Special Features:**

Available with variable speed, speed sensor, and alarm; this item has a third wire (blue) which is a hook-up for the locked motor sensor; weight is 256.0 g.

**Height:**

Between 119.5 millimeters and 120.5 millimeters

**Material:**

Plastic

**Style Designator:**

Fixed

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A087a0