NSN 4210-00-203-2645

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-00-203-2645

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
2.000 inches
Tempurature Rating:
-65.0 degrees fahrenheit and 212.0 degrees fahrenheit single response
Outside Diameter:
2.500 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Burst Test Pressure:
600.0 pounds per square inch
Layer Composition And Location:
Outer layer woven polyester fiber cord
Maximum Operating Pressure:
200.0 pounds per square inch
Thread Size:
2.000 inches 1st end
Hydrostatic Test Pressure:
400.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
300.000 inches excluding end fittings
Media For Which Designed:
Water, fresh single response
Thread Series Designator:
Npsh 2nd end
Specification Data:
81348-zz-h-451 government specification
Specification Or Standard:
3 type and b class
Shelf Life:

N/a

NSN 4210-00-203-2645

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0