

NSN 4210-00-288-6866 Automatic Sprinkler Control Valve - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/4210-00-288-6866 **Body Material: Brass** First End Flange Outside Diameter: 10.125 inches **Maximum Operating Pressure:** 150.0 pounds per square inch **Body Style:** Straight thru Stem Material: Nickel copper alloy Furnished Items: Test attachment and emergency manual operating device **Tempurature Rating:** Not rated Media For Which Designed: Water, fresh **First End Connection Type:** Plain face flange First End Style Designator: Plain First End Flange Shape Style: Round w/o bolt holes First End Flange Thickness: 1.187 inches Second End Relationship With First End: Identical **Seat Material: Brass Face To Face Distance:**

18.750 inches

Flow Control Device:

Disk, flat

Flow Control Device Material:

Rubber

Valve Operation Method:

Piston

End Connection Quantity:

2

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

NSN 4210-00-288-6866

Automatic Sprinkler Control Valve - Page 2 of 2



Renewable Seat Ring Type:
Bonded
Sprinkler System For Which Designed:
Dry pipe
Valve Loading Spring Location:
Internal
Stem Movement Direction:
Ascending
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fila:

A07100