

View Online at <https://aerobasegroup.com/nsn/4210-00-288-6873>

Body Material:

Bronze manganese, mil-b-16261, grade 6

First End Flange Outside Diameter:

5.562 inches

Maximum Operating Pressure:

150.0 pounds per square inch

Body Style:

Straight thru

Stem Material:

Nickel copper alloy, mil-n-894-canceled

Furnished Items:

Cap and chain and emergency opening device and test attachment

Tempurature Rating:

150.0 degrees celsius

Media For Which Designed:

Water, salt

First End Connection Type:

Plain face flange

First End Style Designator:

Plain

First End Flange Shape Style:

Round w/o bolt holes

First End Flange Thickness:

0.562 inches

Second End Relationship With First End:

Identical

Seat Material:

Bronze manganese, mil-b-16261, grade 6

Face To Face Distance:

11.500 inches

Flow Control Device:

Disk, flat

Flow Control Device Material:

Rubber, buna-n and bronze manganese, mil-b-16261, grade 6

Valve Operation Method:

Piston

End Connection Quantity:

2

Bonnet Type:

Inside spring

Bonnet Attachment Method:

Bolted

Renewable Seat Ring Type:

Retaining screw

Sprinkler System For Which Designed:

Dry pipe

Valve Loading Spring Location:

Internal

Stem Movement Direction:

Ascending

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A07100