## NSN 4210-00-289-6123

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-00-289-6123

| Cross Sectional Shape:  |
|---|
| Round   |
| Thread Direction:   |
| Right-hand 1st end  |
| Inside Diameter:  |
| 1.500 inches  |
| Tempurature Rating:   |
| -40.0 degrees fahrenheit and 200.0 degrees fahrenheit single response |
| Minimum Inside Bending Radius:  |
| 3.000 inches  |
| Connection Style:   |
| Swivel nut, gasket seal 1st end                                       |
| End Connection Design:  |
| Straight 2nd end  |
| Connection Type:  |
| Threaded internal hose 1st end  |
| Burst Test Pressure:  |
| 2000.0 pounds per square inch   |
| Layer Composition And Location:                                       |
| Outer layer molded rubber, synthetic                                  |
| Maximum Operating Pressure:   |
| 500.0 pounds per square inch  |
| Thread Size:  |
| 1.500 inches 2nd end  |
| Hydrostatic Test Pressure:  |
| 1000.0 pounds per square inch   |
| Inside Surface Condition:   |
| Smooth  |
| Measuring Method And Length:  |
| 300.000 inches excluding end fittings                                 |
| Media For Which Designed:   |
| Water single response   |
| Thread Series Designator:   |
| Npsh 2nd end  |
| Specification Data:   |
| 81348-zz-h-451 government specification                               |
| Specification Or Standard:  |
| 1 type and b class and 1-1/2 size                                     |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |

--

## NSN 4210-00-289-6123

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



| em |  |  |  |
|----|--|--|--|
|    |  |  |  |
|    |  |  |  |

No

Fiig:

A542a0