NSN 4210-00-372-0853

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-00-372-0853

Cross S	ectional	Shape:
---------	----------	--------

Round

Thread Direction:

Right-hand and left-hand 2nd end

Inside Diameter:

0.500 inches

Tempurature Rating:

-20.0 degrees fahrenheit and 200.0 degrees fahrenheit single response

Outside Diameter:

0.969 inches

Minimum Inside Bending Radius:

4.000 inches

Connection Style:

Threaded 2nd end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal and external pipe 2nd end

Burst Test Pressure:

8000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, chloroprene

Maximum Operating Pressure:

1000.0 pounds per square inch

Thread Size:

0.750 inches and 1.000 inches 2nd end

Hydrostatic Test Pressure:

2000.0 pounds per square inch

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches

Special Features:

Recoil preventor on first end

Media For Which Designed:

Carbon dioxide single response

Thread Series Designator:

Npt and nps 2nd end

Specification Data:

81349-mil-h-16236 government specification

Shelf Life:

N/a

NSN 4210-00-372-0853

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A542a0