NSN 4210-00-423-6750

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-00-423-6750

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
0.312 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response Outside Diameter:
0.719 inches
Minimum Inside Bending Radius:
4.500 inches
Connection Style:
Swivel, plain 1st end
End Connection Design:
Straight 1st end
Connection Type:
Threaded external pipe 1st end
Features Provided:
Perforated outer cover and identical ends
Burst Test Pressure:
10000.0 pounds per square inch
Layer Composition And Location:
1st layer braided corrosion resistant steel wire and outer layer molded rubber, neoprene
Maximum Operating Pressure:
2500.0 pounds per square inch
Thread Size:
0.250 inches 1st end
Seat Angle:
30.0 degrees 1st end
Hydrostatic Test Pressure:
4000.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
72.000 inches
Thread Series Designator:
Npt 1st end
Shelf Life:
N/a
Unit Of Measure:

-

NSN 4210-00-423-6750

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



em			

No

Fiig:

A542a0