NSN 4210-00-541-6230

Cross Sectional Shape:

Specification Or Standard: 1 type and a class and 2-1/2 size

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-00-541-6230

| Round |
|---|
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 2.500 inches |
| Tempurature Rating: |
| -55.0 degrees fahrenheit and 160.0 degrees fahrenheit single response |
| Outside Diameter: |
| 2.543 inches |
| Minimum Inside Bending Radius: |
| 3.250 inches |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal hose 1st end |
| Thready Qty Per Inch (tpi): |
| 7-1/2 2nd end |
| Burst Test Pressure: |
| 700.0 pounds per square inch |
| Layer Composition And Location: |
| 1st layer woven cotton cord |
| Maximum Operating Pressure: |
| 150.0 pounds per square inch |
| Thread Size: |
| 2.500 inches 2nd end |
| Hydrostatic Test Pressure: |
| 350.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Mildew resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 150.000 inches |
| Media For Which Designed: |
| Water, fresh single response |
| Thread Series Designator: |
| Nh 2nd end |

NSN 4210-00-541-6230

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



| Fsc Application Da | ta |
|--------------------|----|
|--------------------|----|

Fire fighting equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0