

View Online at <https://aerobasegroup.com/nsn/4210-00-541-6230>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

2.500 inches

Temperature Rating:

-55.0 degrees fahrenheit and 160.0 degrees fahrenheit single response

Outside Diameter:

2.543 inches

Minimum Inside Bending Radius:

3.250 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal hose 1st end

Thready Qty Per Inch (tpi):

7-1/2 2nd end

Burst Test Pressure:

700.0 pounds per square inch

Layer Composition And Location:

1st layer woven cotton cord

Maximum Operating Pressure:

150.0 pounds per square inch

Thread Size:

2.500 inches 2nd end

Hydrostatic Test Pressure:

350.0 pounds per square inch

Outer Covering Environmental Protection:

Mildew resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

150.000 inches

Media For Which Designed:

Water, fresh single response

Thread Series Designator:

Nh 2nd end

Specification Or Standard:

1 type and a class and 2-1/2 size

Fsc Application Data:

Fire fighting equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0