

View Online at https://aerobasegroup.com/nsn/4210-00-595-1838

| Cross Sectional Shape: |
|---|
| Round |
| Thread Direction: |
| Right-hand 1st end |
| Inside Diameter: |
| 0.750 inches |
| Outside Diameter: |
| 1.375 inches |
| Exterior Color: |
| Black |
| Connection Style: |
| Swivel nut, gasket seal 1st end |
| End Connection Design: |
| Straight 2nd end |
| Connection Type: |
| Threaded internal hose 1st end |
| Layer Composition And Location: |
| Outer layer molded rubber, synthetic |
| Maximum Operating Pressure: |
| 600.0 pounds per square inch |
| Thread Size: |
| 1.000 inches 2nd end |
| Hydrostatic Test Pressure: |
| 2400.0 pounds per square inch |
| Outer Covering Environmental Protection: |
| Abrasion resistant and heat resistant and solvent resistant |
| Inside Surface Condition: |
| Smooth |
| Measuring Method And Length: |
| 600.000 inches |
| Media For Which Designed: |
| Water, fresh single response |
| Thread Series Designator: |
| Npsh 2nd end |
| Specification Data: |
| 04024-185 government standard |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| |

No

NSN 4210-00-595-1838

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



Fiig: A542a0