NSN 4210-00-731-9106

Cross Sectional Shape:

Round

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-00-731-9106

| Round | | | | | | |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|
| Thread Direction: | | | | | | |
| Right-hand 1st end | | | | | | |
| Inside Diameter: | | | | | | |
| 0.250 inches | | | | | | |
| Tempurature Rating: | | | | | | |
| -40.0 degrees fahrenheit single response | | | | | | |
| Outside Diameter: | | | | | | |
| 0.750 inches | | | | | | |
| Quick Disconnect Size: | | | | | | |
| 0.500 inches 2nd end | | | | | | |
| Connection Style: | | | | | | |
| Push (internal) 2nd end | | | | | | |
| End Connection Design: | | | | | | |
| Straight 2nd end | | | | | | |
| Connection Type: | | | | | | |
| Threaded external pipe 1st end | | | | | | |
| Burst Test Pressure: | | | | | | |
| 1000.0 pounds per square inch | | | | | | |
| Layer Composition And Location: | | | | | | |
| Outer layer molded rubber, synthetic | | | | | | |
| Maximum Operating Pressure: | | | | | | |
| | | | | | | |
| 200.0 pounds per square inch | | | | | | |
| 200.0 pounds per square inch Thread Size: | | | | | | |
| | | | | | | |
| Thread Size: | | | | | | |
| Thread Size: 0.375 inches 1st end | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 420.000 inches | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 420.000 inches Special Markings: | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 420.000 inches Special Markings: Pneumatic | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 420.000 inches Special Markings: Pneumatic Media For Which Designed: | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 420.000 inches Special Markings: Pneumatic Media For Which Designed: Air single response | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 420.000 inches Special Markings: Pneumatic Media For Which Designed: Air single response Thread Series Designator: | | | | | | |
| Thread Size: 0.375 inches 1st end Hydrostatic Test Pressure: 400.0 pounds per square inch Outer Covering Environmental Protection: Oil resistant and ozone resistant Inside Surface Condition: Smooth Measuring Method And Length: 420.000 inches Special Markings: Pneumatic Media For Which Designed: Air single response Thread Series Designator: Npt 1st end | | | | | | |

NSN 4210-00-731-9106

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



| | • • | | | | |
|----|-----|-------------|----|-----|------|
| In | 18 | <i>(</i>)+ | МА | 261 | ıre: |
| | | | | | |

--

Demilitarization:

No

Fiig:

A542a0