Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-037-7031

Cross Sectorial Snape: Cross Sectorial Snape: Council Shound Firead Direction: Right-hard 1st and Firead Direction: Right-hard 1st and Firead Diameter: 1.500 inches Connection Style: Connection Style: Connection Design: Connection Design: Straight 2nd and Connection Design: Straight 2nd and Connection Type: Threaded intermal hose 1st and Thready Qty Per Inch (tpi): 9 2nd and End Connection Council Straight 2nd and Composition And Location: 1 Straight 2nd and Composition And Location: 2 Straight 2nd and Composition And Composition 2 Straight 2nd and Composition And Composition 2 Straight 2nd And Location 2 Strai	Green Sectional Shares
Thread Direction: Right-hand 1st end Right-hand 1st end Inside Diameter: 1.500 Inches: Outside Diameter: 1.812 Inches Connection Style: Straight 2nd end End Connection Design: Straight 2nd end Connection Design: Straight 2nd end Thread 2NP tenh (top): 9 2nd end Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1.500 inches 2nd end Hydrostaft Test Pressure: 4.500 pounds per square inch Layer Composition And Location: 1.500 inches 2nd end Hydrostaft Test Pressure: 4.500 pounds per square inch Concovering Environmental Protection: Midew resistant Bide Surface Condition: Simoth Midew resistant Bide Surface Condition: Simoth Midew resistant Bide Surface Condition: Simoth Midew resistant Bide Surface Donsignet: Named Aled	Cross Sectional Shape:
Right-hand 1st and Inside Diameter: 1.50 inches Outside Diameter: 1.312 inches Connection Style: Swied, plain 2nd end End Connection Tope: Triaght 2nd and Connection Type: Threaded internal hose 1st end Threaded internal hose 1st end Burst Test Pressure: 90:00 pounds per square inch Eusy responsition And Location: 1.50 inches 2nd end Hydrostatic Test Pressure: 1.50 onches 2nd end Burst Pressure: 1.50 onches 2nd end Hydrostatic Test Pressure: 1.50 onches 2nd end Burst Pressure: 1.50 onches 2nd end Hydrostatic Test Pressure: 1.50 onches 2nd end Burst Pressure: 1.50 onches 2nd end Hydrostatic Test Pressure: 1.50 onches 2nd end Burst Pressure: 1.50 onches 2nd end Hydrostatic Test Pressure: 1.50 onches 2nd end Hydrostatic Test Pressure:	
Iside Diameter: 1.500 inches Outsich Diameter: 1.812 inches Connection Skyle: Swivel, plain 2nd end End Connection Design: Straight 2nd end Connection Tope: Threaded internal hose 1st end Threaded internal hose 1st end Threaded proven conton cod Burst Pressure: 90.0 points per square inch Layer worve notton cod Thread Stree 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Logo concettory: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Logo inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Builder versitati Inder Versitati Milder versitati Builder versitati Milder versitati Milder versitati Vater single response Concettory Statistic Designato: Nater angle response Contertory	
1.500 inches Duside Diameter: 1.512 inches Connection Style: Swivel, pain 2nd end End Connection Design: Straight 2nd end Connection Design: Straight 2nd end Connection Type: Thread Que Per Inch (up): 9 2nd end Burst Test Pressure: 900 0 pounds per square inch Layer Composition And Location: 1st layer wore toton cord Thread Straight 2nd end Middew resistant Inside Surface Condition: Smoth Measuring Environmental Protection: Middew resistant Inside Surface Condition: Smoth Measuring Method And Longth: Auge Straight 2nd end Straight 2nd end Middew resistant Inside Surface Condition: Smoth Measuring Method And Longth: Auge Straight 2nd end Middew resistant Middew resistant Middew resistant Middew resistant Middew resistant Middew frest Pressure: Auge Straight 2nd Protection: Middew frest Pressure:	
Outside Diameter: 1.812 Inches Connection Style: Swivel, plain 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal hose 1st end Threaded internal hose 1st end Burst Connection App: 92 nd end Burst Connection And Location: 9300 0 points per square inch Layer woven cotton cord Threaded Threasure: 9300 0 points per square inch Layer woven cotton cord Thread Size 1.500 inches 2nd end Hydrostatic Test Pressure: 9300 0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Mildew resistant Milder Sor Which Designed: Water Sub pospinse Thread Series Designator: Na and B Milder Sor Milch Designed: Water Solution Data: Milder Solution Data: Milder Solution Data: Milder Solution Data: Macoutint Data: M	
1.412 lanches Connection Style: Swivel, plain 2nd and End Connection Design: Straight 2nd and Connection Type: Threaded internal hose 1st and Thready Qty Per Inch (tpl): 9 2nd end Burst Tessure: 90.00 pounds per square inch Layer Composition And Location: 1 stal ayer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrosatic Test Pressure: 450.0 pounds per square inch Hydrosatic Test Pressure: 450.0 pounds per square inch Bust Test Pressure: 450.0 pounds per square inch Budew resistant Indew resistant Budies Urale Condition: Smooth Measuring Method And Length: 600.000 inches Melia For Which Designed: Na dell Specification Data: Que24-5100-186 government specification Shell for Mid Messures Vae Na dell Specification Data: Na dell for Messure: N	
Connection Style: Swikel, plain 2nd end End Connection Design: Straight 2nd end Connection Type: Threaded internal hose 1st end Thready QP Princh (pj): 9 2nd end Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1st layer woven cotton cord Thread Strait 1500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Midew resistant Inside Surface Condition: Strait Cest Pressure: 450.0 pounds per square inch Midew resistant Breade Condition: Smooth Measuring Method And Length: Goodo Inches Media For Which Designed: Vater single response Thread Stile: Na Cool Inches Moder Stile Superment specification Sheerline: Na Cool Inches Mice Measure: Na Cool Inches Mice Measure: Na Cool Inches Mice Measure: Na Cool	
Stridght 2nd end Extraight 2nd end Connection Type: Threadded internal hose 1st end Threadd yel nich (tp): 9 2nd end Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1st layer woven cotton cord Thread Size: 1.500 inches 2nd end Midew resistant Bode Schollion: Stoo pounds per square inch Midew resistant Bode Schollion: Stoo pounds per square inch Midew resistant Bode Schollion: Stoo pounds per square inch Midew resistant Bode Schollion: Stoo pounds per square inch Midew resistant Bode Schollion: Stoo pounds per square inch Midew resistant Bode Schollion: Stoo pounds per square inch Midew resistant Bode Schollion: Stoo pounds per square inch Meda For Which Designed: Mode Scholl Schollion: Stoo pounds in the schollion Schollion Scholion Scholion Schollion Schollion Scholion Scholion S	
End Connection Design: Straight 2nd end Connection Type: Threadd internal hose 1st end Thready Qty Per Inch (tpi): 9 2nd end Bust Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1st layer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Udre Covering Environmental Protection: Midew resistant Inside Surface Condition: Sonoth Media For Which Designed: Vater single response Heda For Which Designed: Vater single response Thread Size: Na 2nd end Midew resistant Inside Surface Condition: Sonoth Media For Which Designed: Vater single response Thread Size: Na 2nd end Sonoth: Matter single response Thread Size: Na 2nd end Matter Size: Na 2nd end Sonoth: Son	
Straight 2nd end Connection Type: Threaded internal hose 1st end Thready Qty Per Inch (tp): 9 2nd end Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1 stal layer woven cotton cord Thread Size: 1.500 inches 2nd end Mydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Moder For Which Designed: Water single response Thread Series Designator: Na dend Mage: Moder Jon Designed: Moder Souries Designator: Na dend Mage: Mage: <t< th=""><th></th></t<>	
Non-extion Type: Threaded Internal hose 1st end Thready Qty Per Inch (tpi): 9 2nd end Burst Test Pressure: 9000 pounds per square inch Layer Composition And Location: 1st layer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Milder resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Mela For Which Designed: Vater single response Thread Series Designator: Na dend Specification Data: Vater Single response Shelf Life: Na Vater Single response Thread Series Designator: Na dend Specification Data: Otiot Measure: Na Life Measure: Na Ent If Measure: Na Dir Of Measure: Image: Image:	
Threaded internal hose 1st end Thready Qty Per Inch (tpi): 9 2nd end Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1st ayer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Middew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Thread Series Designator: Nh 2nd end Specification Data: Nu2 And And Specification Data: Nu2 And Specification Da	-
Thready Qiy Per Inch (tpi): 9 2nd end Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1 stayer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Coording Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Media For Which Designed: Wold on ches Pater and Size Na and And Length: G00.000 inches Media For Which Designed: Na and Mark And Length: Vater single response Thread Series Designator: Na and Mark And Length: Audou-foto Pata: Audou-foto Pata: Na and end Specification Data: Na Vata Mark And Length: Na Dit Of Measure: Vata Term Composition Specification Data: Nata Dit Of Measure: Pater Comedia	
92.nd end Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1 Stayer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Instead Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Vald end Smooth Media For Which Designed: Vald end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Nature: Nature: <t< th=""><th></th></t<>	
Burst Test Pressure: 900.0 pounds per square inch Layer Composition And Location: 1st layer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smoth Measuring Method And Length: 600.000 inches Media For Which Designed: Water single response Thread Steine Na 2Method Jacate Specification Data: 04024-5100-186 government specification Shelf Life: N/a Entified Measure: Into Measure: Pacification Data: Pacification Contex	
900.0 pounds per square inchLayer Composition And Location:1st layer woven cotton cordThread Size:1.500 inches 2nd endHydrostatic Test Pressure:450.0 pounds per square inchOuter Covering Environmental Protection:Mildew resistantInside Surface Condition:SmoothMeasuring Method And Length:600.000 inchesMidew resigner:Water single responseThread Series Designator:Nh 2nd endSpecification Data:04024-5100-186 government specificationShelf Life:NaDet If Measure:NaDet If Measure:NaDet If Measure:Image: Measure:Mater Street:Mater Street:<	
Layer Composition And Location: 1st layer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Vater single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: Na Dit Of Measure: Image: Particitation Data: Image: Dit Of Measure: Image: Image: <t< th=""><th></th></t<>	
1st layer woven cotton cord Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Vater single response Thread Series Designator: Na 2nd end Specification Data: 04024-5100-186 government specification Sheff Life: Na Diff Of Measure: Na Diff Of Measure: Teal Encilier Instruction:	
Thread Size: 1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Vater single response Thread Series Designator: Na 2nd end Specification Data: 04024-5100-186 government specification Sheff Life: Na Mid Measure: Na Designet: Na Designet: <td< th=""><th></th></td<>	
1.500 inches 2nd end Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: 600.000 inches Media For Which Designed: Mater single response Thread Series Designator: Na dend Specification Data: 64024-5100-186 government specification Shelf Life: Na Lifo Measure: - -	
Hydrostatic Test Pressure: 450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Vater single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Sheft Life: N/a Und Of Measure: Image: Image: Image: Image:	Thread Size:
450.0 pounds per square inch Outer Covering Environmental Protection: Mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: - -	1.500 inches 2nd end
Outer Covering Environmental Protection:Mildew resistantInside Surface Condition:SmoothMeasuring Method And Length:600.000 inchesMedia For Which Designed:Yater single responseThread Series Designator:Nh 2nd endSpecification Data:604024-5100-186 government specificationShelf Life:N/aUnit of Measure:Demilitarization:	Hydrostatic Test Pressure:
Mildew resistant Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Vater single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure:	450.0 pounds per square inch
Inside Surface Condition: Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: 	Outer Covering Environmental Protection:
Smooth Measuring Method And Length: 600.000 inches Media For Which Designed: Mater single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Inti Of Measure: 	Mildew resistant
Measuring Method And Length:600.000 inchesMedia For Which Designed:Water single responseThread Series Designator:Nh 2nd endSpecification Data:04024-5100-186 government specificationShelf Life:N/aUnit Of Measure:Demilitarization:	Inside Surface Condition:
600.000 inches Media For Which Designed: Water single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: 	Smooth
Media For Which Designed:Water single responseThread Series Designator:Nh 2nd endSpecification Data:04024-5100-186 government specificationShelf Life:N/aUnit Of Measure:Demilitarization:	Measuring Method And Length:
Water single response Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	600.000 inches
Thread Series Designator: Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	Media For Which Designed:
Nh 2nd end Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Specification Data: 04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
04024-5100-186 government specification Shelf Life: N/a Unit Of Measure: Demilitarization:	
Shelf Life: N/a Unit Of Measure: Demilitarization:	Specification Data:
N/a Unit Of Measure: Demilitarization:	
Unit Of Measure: Demilitarization:	Shelf Life:
 Demilitarization:	N/a
Demilitarization:	Unit Of Measure:
No	Demilitarization:
	No

NSN 4210-01-037-7031

Nonmetallic Hose Assembly - Page 2 of 2

Fiig: A542a0

