

View Online at <https://aerobasegroup.com/nsn/4210-01-046-9668>

Prime Mover Quantity:

1

Cylinder Quantity:

6

Length:

Between 14.000 feet and 24.000 feet

Submersibility:

Nonsubmersible and submersible

Prime Mover Type:

Diesel engine

Furnished Items And Quantity:

Ax 2, 10 ft lg 4-1/2 in. Diameter hardsuct hose 2, 16 ft lg 4-1/2 in. Diameter soft suct hose 1, 24 ft ext ladder 1, 14ft roof ladder 1, backpack water exti nguisher 2, co2 exting 1, pike pole 1, crowbar 1, wrecking bar 1, spanner wrench 2, double-eye wrench 2, boltcutter 1, hose and ladder strap 6, lever oerated hose clamp 1, hose jacket 1, lantern 2, strainer 1

Design Type:

Brush and grass and structural

Operation Method:

Manual

Engine Model Number:

6v53n

Engine Manufacturer Name:

Detroit diesel division, gmc corp

Multifuel Usage Feature:

Not provided

Transmission Type:

Any acceptable

Pump Drive Type:

Power take-off

Mounting Location:

Front and rear

Wheel Arrangement Style:

Single wheels, single axle each end

Pump Capacity:

500.0 gallons per minute

Chemical Type:

Foam

Pump Type:

Two stage

Tank Capacity:

600.0 gallons

Extinguishing Agent For Which Designed:

Foam and water

Water Tank Quantity:

1

Chemical Tank Quantity:

1

Chemical Tank Capacity:

55.0 gallons

Aerial Ladder:

Included

Chassis Size Designation:

Any acceptable

Front Wheel Drive Feature:

Included

Chassis Load Rating:

18.0 tons

Wheelbase Size:

163.000 inches

Cab Location:

Any acceptable

Cab Design:

Closed

Gross Weight Range:

+29999.0/+30000.0 pounds

Winch:

Included or not included

Brake Power Rating:

Not rated

Special Features:

With tilt cab, insulated for minus 20 degrees f operation, non-winterized

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

T278-a