## NSN 4210-01-064-3449

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-064-3449
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.000 inches
Tempurature Rating:
-40.0 degrees fahrenheit single response and 200.0 degrees fahrenheit single response
Outside Diameter:
1.547 inches
Minimum Inside Bending Radius:
8.000 inches
Exterior Color:
Black
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Features Provided:
Reusable end fittings
Thready Qty Per Inch (tpi):
8 2nd end
Burst Test Pressure:
2250.0 pounds per square inch
Layer Composition And Location:
Outer layer molded rubber, synthetic err-100
Maximum Operating Pressure:
565.0 pounds per square inch
Thread Size:
1.375 inches 2nd end
Hudractatic Test Deserves

#### **Hydrostatic Test Pressure:**

1125.0 pounds per square inch

## **Outer Covering Environmental Protection:**

Abrasion resistant and oil resistant

### Inside Surface Condition:

Smooth

#### **Measuring Method And Length:**

600.000 inches excluding end fittings

#### Media For Which Designed:

Chemical single response

# NSN 4210-01-064-3449

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



<b>Thread Series Designator:</b>
Nh 2nd end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A542a0