

View Online at <https://aerobasegroup.com/nsn/4210-01-076-8203>

**Cross Sectional Shape:**

Round

**Thread Direction:**

Right-hand 1st end

**Inside Diameter:**

0.750 inches

**Minimum Inside Bending Radius:**

7.500 inches

**Connection Style:**

Swivel nut, gasket seal 1st end

**End Connection Design:**

Straight 2nd end

**Connection Type:**

Threaded internal hose 1st end

**Features Provided:**

Perforated outer cover

**Thready Qty Per Inch (tpi):**

11-1/2 2nd end

**Burst Test Pressure:**

1000.0 pounds per square inch

**Layer Composition And Location:**

Outer layer molded rubber, ethylene propylene diene err-100

**Maximum Operating Pressure:**

250.0 pounds per square inch

**Thread Size:**

0.750 inches 2nd end

**Hydrostatic Test Pressure:**

500.0 pounds per square inch

**Outer Covering Environmental Protection:**

Heat resistant

**Inside Surface Condition:**

Smooth

**Measuring Method And Length:**

600.000 inches working

**Special Features:**

Noncollapsible

**Thread Series Designator:**

Nh 2nd end

**Specification Data:**

81349-mil-h-24580/sh/ government specification

**Specification Or Standard:**

B type and 3/4 in. Size

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A542a0