

View Online at <https://aerobasegroup.com/nsn/4210-01-076-8203>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

0.750 inches

Minimum Inside Bending Radius:

7.500 inches

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal hose 1st end

Features Provided:

Perforated outer cover

Thready Qty Per Inch (tpi):

11-1/2 2nd end

Burst Test Pressure:

1000.0 pounds per square inch

Layer Composition And Location:

Outer layer molded rubber, ethylene propylene diene err-100

Maximum Operating Pressure:

250.0 pounds per square inch

Thread Size:

0.750 inches 2nd end

Hydrostatic Test Pressure:

500.0 pounds per square inch

Outer Covering Environmental Protection:

Heat resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

600.000 inches working

Special Features:

Noncollapsible

Thread Series Designator:

Nh 2nd end

Specification Data:

81349-mil-h-24580/sh/ government specification

Specification Or Standard:

B type and 3/4 in. Size

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0