Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-131-0247

Crees Sectional Shape
Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
2.500 inches
Tempurature Rating:
-55.0 degrees fahrenheit single response and 180.0 degrees fahrenheit single response
Outside Diameter:
2.540 inches
Minimum Inside Bending Radius:
3.250 inches
Quick Disconnect Size:
2.500 inches 2nd end
Connection Style:
Push (internal) 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Internal quick disconnect 1st end
Thready Qty Per Inch (tpi):
7-1/2 2nd end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer molded rubber, synthetic err-100
Maximum Operating Pressure:
300.0 pounds per square inch
Thread Size:
2.500 inches 2nd end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Inside Surface Condition:
Smooth
Measuring Method And Length:
600.000 inches excluding end fittings
Media For Which Designed:
Water single response
Thread Series Designator:
Nh 2nd end
Specification Data:
81349-mil-h-24606 government specification

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A542a0