

View Online at <https://aerobasegroup.com/nsn/4210-01-264-3871>

Cross Sectional Shape:

Round

Thread Direction:

Right-hand 1st end

Inside Diameter:

1.500 inches

Unable To Decode:

Unable to decode or unable to decode

Exterior Color:

Orange

End Application:

Ticonderoga class cg (47); wasp class lhd; forrestal class cv; nimitz class cvn; sturgeon class ssn (637); virginia class cgn (41); los angeles class ssn (688); tarawa class lha; oliver perry class ffg

Connection Style:

Swivel nut, gasket seal 1st end

End Connection Design:

Straight 2nd end

Connection Type:

Threaded internal hose 1st end

Burst Test Pressure:

900.0 pounds per square inch

Layer Composition And Location:

1st layer woven polyester fiber cord err-100

Thread Size:

1.500 inches 2nd end

Hydrostatic Test Pressure:

600.0 pounds per square inch

Outer Covering Environmental Protection:

Abrasion resistant and cold resistant and ozone resistant

Inside Surface Condition:

Smooth

Measuring Method And Length:

25.0 feet excluding end fittings

Special Features:

Includes gaskets

Media For Which Designed:

Water single response

Thread Series Designator:

Npsh 2nd end

Specification Data:

81349-mil-h-24606 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A542a0