## NSN 4210-01-264-3871

Fire Fighting Nonmetallic Hose Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/4210-01-264-3871

Cross Sectional Shape:
Round
Thread Direction:
Right-hand 1st end
Inside Diameter:
1.500 inches
Unable To Decode:
Unable to decode or unable to decode
Exterior Color:
Orange
End Application:
Ticonderoga class cg (47); wasp class lhd; forrestal class cv; nimitz class cvn; sturgeon class ssn (637); virginia class cgn (41); los
angeles class ssn (688); tarawa class lha; oliver perry class ffg
Connection Style:
Swivel nut, gasket seal 1st end
End Connection Design:
Straight 2nd end
Connection Type:
Threaded internal hose 1st end
Burst Test Pressure:
900.0 pounds per square inch
Layer Composition And Location:
1st layer woven polyester fiber cord err-100
Thread Size:
1.500 inches 2nd end
Hydrostatic Test Pressure:
600.0 pounds per square inch
Outer Covering Environmental Protection:
Abrasion resistant and cold resistant and ozone resistant
Inside Surface Condition:
Smooth
Measuring Method And Length:
25.0 feet excluding end fittings
Special Features:
Includes gaskets
Media For Which Designed:
Water single response
Thread Series Designator:
Npsh 2nd end
Specification Data:

N/a

Shelf Life:

81349-mil-h-24606 government specification

## NSN 4210-01-264-3871

Fire Fighting Nonmetallic Hose Assembly - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A542a0