

View Online at <https://aerobasegroup.com/nsn/4210-01-290-8755>

Prime Mover Quantity:

1

Cylinder Quantity:

8

Length:

100.000 feet

Submersibility:

Nonsubmersible

Prime Mover Type:

Diesel engine

Furnished Items And Quantity:

Chrom-plated spotlight for left and right side of windshield 2; engine compartment lights for illuminating both sides of engine 2; emer flashing red lt 1; lt at base of ladder 1; 50 ft alumalum ext ladder 1, 35 ft alum ext ladder 2; 28 ft alum ext ladder 1; 14 ft alumext ladder 1; 10 ft collapsible ladder 1; 20 ft sgl ladder w/unfold roof hooks1, hyd/manual ground jacks 2 and wheel chocks 4

Design Type:

Rescue and structural

Operation Method:

Hydraulic motor

Reverse Speed Quantity:

1

Transmission Type:

Automatic

Speed Range Quantity:

1

Forward Speed Quantity Per Range:

4

Wheel Arrangement Style:

Dual wheels, single axle one end, single wheels, single axle opposite end

Extinguishing Agent For Which Designed:

Foam and water

Aerial Ladder:

Included

Chassis Size Designation:

4x2

Front Wheel Drive Feature:

Not included

Cab Location:

Ahead of engine

Cab Design:

Closed

Winch:

Not included

Special Features:

Cylinder quantity is min, oscillating type fifth wheel mounted at rear of tractor frame, equipped w/12v starting ignition and lighting system, equipped w/a 2 wheel semitrailer drawn by a tractor 4 by 2 chassis. tractor is frontwheel steerable. engine shall develop not less than 250hbp

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

T278-a